


CRF 10,18,14,12,01

- Reflow & Wave Solderable
- Performs like RMC under normal conditions
- Fuses when overloaded
- Anti-leaching Nickel barrier & 90/10 Solder Plated Terminations are standard
- Three (3) Digit Black Mark on Brown Protective Coating

Standard E-24 (5%) Decade Values

1.0	1.1	1.2	1.3	1.5	1.6	1.8	2.0	2.2	2.4	2.7	3.0
3.3	3.6	3.9	4.3	4.7	5.1	5.6	6.2	6.8	7.5	8.2	9.1

Dimensions: (mm)



Type	L±0.2	W	C	d ^{±0.2} _{-0.1}	t±0.1
CRF10	2.0	1.25±0.1	0.4±0.2	0.3	0.5
CRF18	3.2	1.6±0.2	0.5±0.3	0.4	0.6
CRF14		2.6±0.2			
CRF12	5.0	2.5±0.2			
CRF01	6.3	3.1±0.2			

STANDARD APPLICATIONS

PART DESIGNATION	POWER RATING @ 70°C	TCR (ppm/°C) Max.	RESISTANCE RANGE E-24***	RESISTANCE TOLERANCE	MAX. OPEN CIRCUIT VOLTAGE	FUSING CHARACTERISTICS FUSING POWER					OPER. TEMP. RANGE	MAX. FUSING TIME
						3.0W 0.2-0.47	2.6W 0.51-1.0	2.4W 1.1-20	2.0W 22-100	1.75W 110-510		
CRF 10	100mW	±1000 (0.2-4.3)	0.2 - 510	J(±5%)	50V	3.75W 0.2-0.47	2.875W 0.51-1.0	2.5W 12-24	2.2W 27-100	2.0W 110-510	-55°C to +125°C	60 sec.
CRF 18	125mW					4.5W 0.2-0.47	4.1W 0.51-1.0	3.5W 5.1-27	3.2W 30-100	3.0W 110-510		
CRF 14	250mW	5.5W 0.2-0.47				5.0W 0.51-1.0	4.0W 5.1-27	3.5W 30-100	3.2W 110-510			
CRF 12	500mW	±500 (4.7-510)			100V	6.5W 0.2-0.47	6.0W 0.51-1.0	5.0W 5.1-30	4.5W 33-100	4.0W 110-510		
CRF 01	1000mW											

Part Numbering System

CRF 10 — 100 J T

Product Type
Chip Resistor Fusing

SIZE	
CODE	WATTAGE (SIZE)
10	1/10 watt (0805)
18	1/8 watt (1206)
14	1/4 watt (1210)
12	1/2 watt (2010)
01	1.0 watt (2512)

Resistance Value E-24
2 significant digits and 1 multiplier, R indicates decimal on values <10

TOLERANCE	
CODE	%
J	±5%

Packaging		
CODE	DETAIL	Qty/Package
B	Bulk	1000 pcs.
T	Tape & Reel (paper carrier)	5000 pcs.
TE	Tape & Reel (plastic carrier)	4000 pcs.

Please refer to packaging explanation on page 6.

