



TABLE I - STANDARD SPECIFICATIONS

Unit: mm

WORKING VOLTAGE	DISC		LEAD		
	DIAMETER	THICKNESS	CODE 6: SPACING	LENGTH (for Figures A, H, I)	DIAMETER (dØ)
12V - 50V 100V	1 - 5	3.0	2.5	25.4	0.48
	5.1 - 15	3.0	5.0	25.4	0.48
	15.1	3.0	9.5	25.4	0.65
500V	1 - 7	4.0	5.0	25.4	0.65
	7.1 - 10	4.0	6.35	25.4	0.65
	10.1 - 25	4.0	9.5	25.4	0.65
1KV	1 - 10	4.0	6.35	25.4	0.65
	10.1 - 25	4.0	9.5	25.4	0.65

* Other spacing and lead diameter available upon request

EXAMPLES:

Ceramic Disc Capacitor 1000pF / 1000 Volts / 10% / Z5U / Lead Spacing 5.0 mm / Tape & Reel Kinked Style /

CODES	(1)	(2)	(3)	(4)	(5)	(6)	(7)
PART #	CCD	G	E	102	K	5	KR

Ceramic Disc Capacitor 68pF / 100 Volts / 5% / NPO / Bulk / Lead Spacing 5.0mm / Lead Style Figure F / Lead Length = 42 mm

NOTE: Non-Standard Lead Length Required

CODES	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
PART #	CCD	E	N	680	J	5	F	42

Ceramic Disc Capacitor 0.01µF / 500 Volts / 20% / Z5U / Bulk / Lead Spacing 6.0mm / Lead Style Figure A

CODES	(1)	(2)	(3)	(4)	(5)	(6)	(7)
PART #	CCD	F	E	103	M	6	A

Ceramic Disc Capacitor 3300pF / 100 Volts / 10% / YPF / Lead Spacing 5.0 mm / Tape & Ammo Kinked Style

CODES	(1)	(2)	(3)	(4)	(5)	(6)	(7)
PART #	CCD	E	L	332	K	5	KA

"TYPE" ON THE NEXT PAGES INCLUDE THE FOLLOWING INFORMATION TO HELP YOU BUILD A PART NUMBER

* EXAMPLE: TYPE DN-120J (from Page 43)

CODE	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
PART #	CCD	D	N	120	J	<input type="text"/>	<input type="text"/>	<input type="text"/>

AS PER CUSTOMER'S REQUIREMENT