

111-02015



Article Number: 111-02015

Description: Standard Cable Tie, 8" Long, UL Rated, 18lb Tensile Strength, PA66, Black, 1000/pkg

Base Data	Local Order Number	T18L0M4
	Type	T18L
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
	Quantity Per	bag
	Brand Family	T-Series
	Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	GLOBAL PART NAME	T18L-PA66-BK
	Short Description	Standard Cable Tie, 8" Long, UL Rated, 18lb Tensile Strength, PA66, Black, 1000/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		80.0N
Length L (Imperial)		8.0"
Length L (Metric)		205.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.10"
Width W (Metric)		2.5mm
Bundle Diameter Min. (Imperial)		0.06"

111-02015



Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	2.17"
	Bundle Diameter Max. (Metric)	55.0mm
	Thickness T (Metric)	1.1mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogen Free	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Listed (US)	Yes
	UL Listed (US and Canada)	Yes
	UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987