





IFQC Series

Specifications

Maximum Electrical Rating: 75°C, 300 Volts Max.
 Insulation Material: Vinyl
 Terminal Material: Brass
 Double Crimp: With Copper Sleeve on Barrel
 Certification: UL/CUL/CSA



Color	Part #	Wire Range Gauge	Maximum Electric Current	Tab Size	Dimensions (mm)			
					B	L	L1	Terminal Barrel I.D.
	IFQC22-16AWG-0.110	22-16 AWG	10 Amps	0.110"	3.8	19.5	15.0	1.7
	IFQC22-16AWG-0.187			0.187"	5.6	19.0	14.0	
	IFQC22-16AWG-0.250			0.250"	7.4	21.0	14.0	
	IFQC16-14AWG-0.110	16-14 AWG	15 Amps	0.110"	3.8	19.0	14.0	2.3
	IFQC16-14AWG-0.187			0.187"	5.6	19.0	14.0	
	IFQC16-14AWG-0.250			0.250"	7.4	21.0	16.0	
	IFQC12-10AWG-0.250	12-10 AWG	24 Amps	0.250"	7.4	21.0	16.0	3.4

General Tolerance	
X. ± 0.50	X.° ± 5°
.X ± 0.20	.X° ± 2°
.XX ± 0.10	.XX° ± 1°
Units : mm	